

Tabulka pro rovnoměrné zatížení polic v [kg]

DÉLKA POLICE ►		600 mm	900 mm				1050 mm				1200 mm				1350 mm			1500 mm						1650 mm			1800 mm			
TYP NOSNÍKU ►		S1	SO	S1	S2	S3	SO	S1	S2	S3	SO	S1	S2	S3	S1	S2	S3	S1	S2	S3	S1G	S2G	S3G	S1	S2	S3	S3	S1G	S2G	S3G
HLOUBKA POLICE ▼	TYP POLICE ▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼
320 mm ►	KOVOVA H12	200	200	280	305	305	170	235	335	370	150	205	275	320	180	220	255	145	175	205	350	360	370	120	145	170	140	310	330	350
	VANOVA	175	200	270	270	270	—	—	—	—	150	205	275	320	—	—	—	145	175	205	350	450	450	—	—	—	140	310	430	530
	PLASTOVA	90	135	135	135	135	150	150	150	150	150	180	180	180	180	200	200	145	175	205	220	220	220	120	145	170	140	270	270	270
400 mm ►	KOVOVA H12	200	200	235	235	235	170	235	275	280	150	205	275	320	180	220	255	145	175	205	350	360	370	120	145	170	140	310	330	350
	KOVOVA H25/A	200	200	280	390	450	170	235	335	385	150	205	275	320	180	220	255	145	175	205	350	520	640	120	145	170	140	310	430	530
	PERFOROVANA H25/C	200	200	280	390	450	—	—	—	—	150	205	275	320	—	—	—	145	175	205	350	520	640	—	—	—	140	310	430	530
	VANOVA	180	200	270	270	270	—	—	—	—	150	205	275	320	—	—	—	145	175	205	350	450	450	—	—	—	140	310	430	530
	PLASTOVA	90	135	135	135	135	150	150	150	150	150	180	180	180	180	200	200	145	175	205	220	220	220	120	145	170	140	270	270	270
	NA PNEUMATIKY	200	—	280	—	450	—	235	—	385	—	205	—	320	180	—	255	145	—	205	—	—	—	120	—	170	140	—	—	—
500 mm ►	KOVOVA H12	185	185	185	185	185	170	230	230	230	150	205	260	260	180	220	255	145	175	205	315	315	315	120	145	170	140	310	320	330
	KOVOVA H25/A	200	200	280	390	420	170	235	335	370	150	205	275	320	180	220	255	145	175	205	350	520	640	120	145	170	140	310	430	530
	PERFOROVANA H25/C	200	200	280	390	450	—	—	—	—	150	205	275	320	—	—	—	145	175	205	350	520	640	—	—	—	140	310	430	530
	VANOVA	140	200	210	210	210	—	—	—	—	150	205	275	280	—	—	—	145	175	205	350	350	350	—	—	—	140	310	420	420
	PLASTOVA	90	135	135	135	135	150	150	150	150	150	180	180	180	180	200	200	145	175	205	220	220	220	120	145	170	140	270	270	270
	NA PNEUMATIKY	200	—	280	—	450	—	235	—	370	—	205	—	320	180	—	255	145	—	205	—	—	—	120	—	170	140	—	—	—
600 mm ►	KOVOVA H12	150	150	150	150	150	170	180	180	180	150	205	210	210	180	220	230	145	175	205	260	260	260	120	145	170	140	305	305	305
	KOVOVA H25/A	200	200	280	350	350	170	235	320	340	150	205	275	320	180	220	255	145	175	205	350	520	640	120	145	170	140	310	430	530
	PERFOROVANA H25/C	200	200	280	360	360	—	—	—	—	150	205	275	320	—	—	—	145	175	205	350	520	600	—	—	—	140	310	430	530
	VANOVA	130	195	195	195	195	—	—	—	—	150	205	260	260	—	—	—	145	175	205	325	325	325	—	—	—	140	310	390	390
	PLASTOVA	60	90	90	90	90	110	110	110	110	120	120	120	120	140	140	140	145	150	150	150	150	150	120	145	170	140	180	180	180
	NA PNEUMATIKY	200	—	280	—	450	—	235	—	370	—	205	—	320	180	—	255	145	—	205	—	—	—	120	—	170	140	—	—	—
700 mm ►	KOVOVA H12	130	130	130	130	130	155	150	150	150	150	180	180	180	180	200	200	145	175	205	220	220	220	120	145	170	140	260	260	260
	KOVOVA H25/A	180	200	280	280	280	170	235	280	300	150	205	275	320	180	220	255	145	175	205	350	520	480	120	145	170	140	310	430	530
	PERFOROVANA H25/C	190	200	280	280	280	—	—	—	—	150	205	275	320	—	—	—	145	175	205	350	480	480	—	—	—	140	310	430	530
	VANOVA	120	180	180	180	180	—	—	—	—	150	205	240	240	—	—	—	145	175	205	300	300	300	—	—	—	140	310	360	360
800 mm ►	KOVOVA H25/A	200	200	230	230	230	170	200	240	260	150	180	250	290	150	200	240	130	160	180	350	425	430	120	145	150	130	310	350	480
	PERFOROVANA H25/C	140	210	210	210	210	—	—	—	—	150	205	275	280	—	—	—	145	175	205	350	350	350	—	—	—	140	310	420	420
	VANOVA	120	180	180	180	180	—	—	—	—	150	205	240	240	—	—	—	145	175	205	300	300	300	—	—	—	140	310	360	360
OVALNÉ NOSNÍKY ►		—	175				—				120				—			130						—			—			

TYP RÁMU ►	SUPER SO	SUPER S1	SUPER S2	SUPER S3	UNIRACK USA	UNIRACK USB
NOSNOST RÁMU ►	1100	1500	2000	3600	2600	3000

